

## [2016-New 642-999 Real Test Questions Free Download From Lead2pass (144-154)]

2016 July Cisco Official New Released 642-999 Q&As in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! This dump is valid to pass Cisco 642-999. And don't just memorize the answer, you need to get through understanding of it because the question changed a little in the real exam. The material is to supplement your studies. Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/642-999.html> QUESTION 144 Which three parameters can be configured for a vHBA? (Choose three.) A. Enable persistent binding. B. Enable a hardware-based failover. C. Define a SAN pin group. D. Assign a QoS policy. E. Define an MTU. F. Assign a MAC address. Answer: ACDE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1\\_chapter\\_011010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-1/b_UCSM_GUI_Configuration_Guide_2_1/b_UCSM_GUI_Configuration_Guide_2_1_chapter_011010.html) QUESTION 145 With Cisco UCS Manager, in which location do you monitor the chassis discovery process? A. CMCB. FSMC. CDPD. DME Answer: B Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_0100011.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_0100011.html) QUESTION 146 Which two protocols does the Cisco Integrated Management Controller support for managing standalone Cisco UCS -Series servers? (Choose two.) A. SoL. B. IPMI. C. IPMIv2. D. SMASH CLPE. E. SNMPv3 Answer: CE Explanation:

<http://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/at-a-glance-c45-737177.pdf> QUESTION 147 Which three statements about what occurs when a Cisco UCS -Series Blade Server connects to the SAN across a fabric interconnect that is enabled in Fibre Channel NPV mode are true? (Choose three.) A. The server ports in F Port mode are pinned to the NP Ports. B. The E Ports are pinned to the E Ports on the fabric interconnect. C. Zoning is deployed on the fabric interconnect. D. The fabric interconnect is not assigned a Fibre Channel domain ID. E. Traffic that is received on the server ports in F Port mode from the server side is pinned to the NPIV-enabled uplink ports on the fabric interconnect. F. The fabric interconnect must have the Fibre Channel uplink port connected to the upstream switch F Port in NPIV mode that performs the Fibre Channel forwarder function. Answer: ADE QUESTION 148 You plan to implement FCoE on a Cisco UCS -Series server. Which option must you configure from the Cisco Integrated Management Controller GUI? A. a vNIC failover. B. a boot table entry. C. NIVD. D. FIP mode Answer: D Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/gui/config/guide/1-2-1/b\\_Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1/Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1\\_chapter9.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/gui/config/guide/1-2-1/b_Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1/Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1_chapter9.html) QUESTION 149 Refer to the exhibit. Which tables correctly map the HIF ports to active FEX NIF ports on a Cisco UCS 2208X IOM in discrete pinning mode?

<b>Table 1</b> 1 - Fabric uplink interface active	All the HIF ports are pinned to the uplink interface
<b>Table 2</b> 2 - Fabric uplink interfaces active	HIF Ports : 1,2,3,4 to uplink interface HIF Ports: 5,6,7,8 to uplink interface
<b>Table 3</b> 4 - Fabric uplink interfaces active	HIF Ports: 1,8 to uplink interface HIF Ports: 2,3 to uplink interface HIF Ports: 6,7 to uplink interface HIF Ports: 4,5 to uplink interface
<b>Table 4</b> 8 - Fabric uplink interfaces active	HIF Port: 1 to uplink interface 1 HIF Port: 2 to uplink interface 2 HIF Port: 3 to uplink interface 3 HIF Port: 4 to uplink interface 4 HIF Port: 5 to uplink interface 5 HIF Port: 6 to uplink interface 6 HIF Port: 7 to uplink interface 7 HIF Port: 8 to uplink interface 8

A. Table 2 and Table 4. B. Table 1 and Table 4. C. Table 2 and Table 3. D. Table 1 and Table 2. E. Table 3 and Table 4. Answer: B Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

[ml](#) QUESTION 150 You have a Cisco UCS C-Series Server. What can you use to log the blade server statistics? A. the Cisco Integrated Management Controller log B. RADIUS C. LDAP D. the XML API Answer: A Explanation:

<http://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/datasheet-c78-733571.html>

QUESTION 151 You manage Cisco UCS -Series Rack-Mount Servers. Which three components can you upgrade by using the Cisco Host Upgrade Utility? (Choose three.) A. the LAN on motherboard B. the Cisco Integrated Management Controller C. the operating system images D. the system BIOS E. the fabric interconnects F. the FEX modules Answer: ABDE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/lomug/2-0-x/b\\_huu\\_2\\_0\\_3/b\\_huu\\_2\\_0\\_3\\_chapter\\_01.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/lomug/2-0-x/b_huu_2_0_3/b_huu_2_0_3_chapter_01.html)

QUESTION 152 Which three components are parts of the Cisco UCS -Series Blade Server software bundle? (Choose three.) A. the adapter firmware B. the Kernel and system firmware for fabric interconnects C. the BIOS firmware D. the IOM firmware E. the Cisco UCS Manager software F. the board controller firmware Answer: ACF Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/firmware-mgmt/gui/2-2/b\\_GUI\\_Firmware\\_Management\\_22/b\\_GUI\\_Firmware\\_Management\\_22\\_chapter\\_0100.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/firmware-mgmt/gui/2-2/b_GUI_Firmware_Management_22/b_GUI_Firmware_Management_22_chapter_0100.html)

QUESTION 153 Which slot(s) contain DIMMs in a 1DPC configuration on Cisco UCS blade server? A. 0 B. 1 and 2 only C. 1 D. 2 Answer: CE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/hw/blade-servers/install/B200.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/hw/blade-servers/install/B200.html)

QUESTION 154 Which destination(s) are valid for syslog messages for a Cisco UCS Fabric Interconnect? A. a file and monitor only B. the log, the monitor and syslog queue C. the console D. the console and log only E. a file F. the console, the monitor, and a file Answer: FE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/ucsm\\_syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog\\_chapter\\_010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/ucsm_syslog/b_Monitoring_Cisco_UCSM_Using_Syslog/b_Monitoring_Cisco_UCSM_Using_Syslog_chapter_010.html)

About 90% questions are from this 642-999 dump. One thing you need to pay attention is the questions are rephrased in the real 642-999 exam. And btw selections are jumbled so you must remember the answer itself not the letter of choice. 2016 Cisco 642-999 exam dumps (All 175 Q&As) from Lead2pass:

<http://www.lead2pass.com/642-999.html> [100% Exam Pass Guaranteed!!!]