

## [2016-New Cisco New Exam 400-101 VCE Files Free Instant Download (1070-1080)]

2016 July Cisco Official New Released 400-101 Q&As in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! After purchasing the dumps for the 400-101 Exam from Lead2pass, I had no doubt that I'd easily pass the exam. Bundle of thanks to Lead2pass for helping me pass the exam without any troubles. Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/400-101.html>

QUESTION 1070 A network engineer is extending a LAN segment between two geographically separated data centers. Which enhancement to a spanning-tree design prevents unnecessary traffic from crossing the extended LAN segment? A. Modify the spanning-tree priorities to dictate the traffic flow. B. Create a Layer 3 transit VLAN to segment the traffic between the sites. C. Use VTP pruning on the trunk interfaces. D. Configure manual trunk pruning between the two locations. Answer: C

QUESTION 1071 The OSPF database of a router shows LSA types 1, 2, 3 and 7 only. Which type of area is this router connected to? A. backbone area B. totally stubby area C. stub area D. not-so-stubby area Answer: D

QUESTION 1072 Which feature can you implement to most effectively protect customer traffic in a rate-limited WAN Ethernet service? A. HCBWFQ B. IntServ with RSVP C. DiffServ D. The IPsec VTI qos pre-classify command E. Q-in-Q Answer: A

QUESTION 1073 An engineer has configured a router to use EUI-64, and was asked to document the IPv6 address of the router. The router has the following interface parameters: mac address C601.420F.0007 subnet 2001:DB8:0:1::/64 A. 2001:DB8:0:1:C601:42FF:FE0F:7 B. 2001:DB8:0:1:FFFF:C601:420F:7 C. 2001:DB8:0:1:FE80:C601:420F:7 D. 2001:DB8:0:1:C601:42FE:800F:7 Answer: A

QUESTION 1074 Which command configures port security on a switch to enable permanent MAC address learning on the interface? A. switchport port-security mac-address-learning enable B. switchport port-security mac-address timer 0 C. switchport port-security mac-address sticky D. switchport port-security mac-address maximum 1 sticky E. switchport port-security mac-address permanent Answer: C

QUESTION 1075 If EIGRP and OSPF are configured within an administrative domain for the same network, which value can you change so that the OSPF becomes the installed routing protocol for all routes? A. Local preference B. Metric C. MED D. Administrative distance E. Prefix length Answer: E

QUESTION 1076 Which three components are in an MPLS header? (choose three) A. a 4-bit experimental use field B. a 4-bit label stack entry C. an 8-bit TTL D. a 2-bottom of stack E. a 3-bit experimental use field F. a 20-bit label Answer: CEF

QUESTION 1077 What is the main function of VRF-lite? A. To allow devices to use labels to make Layer 2 Path decisions B. To segregate multiple routing tables on a single device C. To connect different autonomous systems together to share routes D. To route IPv6 traffic across an IPv4 backbone Answer: B

QUESTION 1078 Refer to the exhibit. Which prefixes will have their distance changed?

```
router eigrp 100
 network 10.0.0.0
 distance 80 10.1.12.0 0.0.0.255 10
 !
 access-list 10 permit ip 10.0.0.0 0.0.0.255 10.0.0.0 0.0.0.255
```

A. all prefixes matching access-list 10 learned from peers in the range 10.1.12.0- 10.1.12.255 B. all internal prefixes in the range 10.1.12.0-10.1.12.255 learned from peers matching access-list 10. C. all internal prefixes matching access-list 10 learned from peers in the range 10.1.12.0- 10.1.12.255 D. all prefixes in the range 10.1.12.0-10.1.12.255 learned from peers matching access-list Answer: C

QUESTION 1079 Which two methods do IPsec VTIs used to identify and transmit encrypted traffic through the tunnel? (choose two) A. static routing B. dynamic routing C. object groups D. ACLs E. NAT Answer: AB

QUESTION 1080 When you deploy DMVPN, what is the purpose of the command crypto isakmp key ciscotest address 0.0.0.0 0.0.0.0 ? A. It is configured on hub and spoke router to establish peering B. It is configured on hub to set the pre-shared key for the spoke routers C. It is configured on the spokes to indicate the hub router D. It is configured on the Internet PE routers to allow traffic to traverse the ISP core Answer: B

I understood all of the questions very easily. I scored 96% on my first try. I am definitely going to spread the word amongst friends and colleagues. Keep up the great work. 2016 Cisco 400-101 exam dumps (All 1119 Q&As) from Lead2pass: <http://www.lead2pass.com/400-101.html> [100% Exam Pass Guaranteed!!!]