

## [2017 New Lead2pass 200-310 New Questions Free Download (41-60)]

2017 June Cisco Official New Released 200-310 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! I was very confused about selecting the best practice test website when preparing for my 200-310 certification exam. Luckily, a friend told me about Lead2pass.com. I passed the 200-310 exam from the first try. Excellent website for free exam dumps! Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/200-310.html>

**QUESTION 41** Which three sources does a network designer use to collect information for characterizing an existing network? (Choose three.)  
A. staff input  
B. visual inventory  
C. network audit  
D. traffic analysis  
E. server statistics  
Answer: ACD

**QUESTION 42** What is the primary consideration when choosing a routed network design over a traditional campus network design?  
A. Layer 3 service support at the network edge  
B. the routing protocol choice: open (OSPF) or proprietary (EIGRP)  
C. the routing abilities of the host devices  
D. the need to control the broadcast domains within the campus core  
Answer: A

**QUESTION 43** Which statement is true concerning the data center access layer design?  
A. The access layer in the data center is typically built at Layer 3, which allows for better sharing of services across multiple servers.  
B. With Layer 2 access, the default gateway for the servers can be configured at the access or aggregation layer.  
C. A dual-homing NIC requires a VLAN or trunk between the two access switches to support the dual IP addresses on the two server links to two separate switches.  
D. The access layer is normally not required, as dual homing is standard from the servers to the aggregation layer.  
Answer: B

**QUESTION 44** Which statement is true concerning the data center distribution (aggregation) layer design?  
A. With Layer 3 at the aggregation layer, the physical loops in the topology must still be managed by STP.  
B. The boundary between Layer 2 and Layer 3 must reside in the multilayer switches, independent of any other devices.  
C. A mix of both Layer 2 and Layer 3 access is the most optimal.  
D. In a small data center, the aggregation layer can connect directly to the campus core, exchanging IP routes and MAC address tables.  
Answer: C

**QUESTION 45** When considering the three VoIP design models - single site, centralized multisite, and distributed multisite - which question below would help to eliminate one of the options?  
A. Will the switches be required to provide inline power?  
B. Will users need to make offsite calls, beyond the enterprise?  
C. Will users require applications such as voice mail and interactive voice response?  
D. Are there users whose only enterprise access is via a QoS-enabled WAN?  
Answer: D

**QUESTION 46** With deterministic Wireless LAN Controller redundancy design, the different options available to the designer have their own strengths. Which statement is an example of such a strength?  
A. Dynamic load balancing, or salt-and-pepper access point design, avoids the potential impact of oversubscription on aggregate network performance.  
B. N+N redundancy configuration allows logically grouping access points on controllers to minimize intercontroller roaming events.  
C. N+N+1 redundancy configuration has the least impact to system management because all of the controllers are colocated in an NOC or data center.  
D. N+1 redundancy configuration uses Layer 3 intercontroller roaming, maintaining traffic on the same subnet for more efficiency.  
Answer: B

**QUESTION 47** When there is a need for immunity to EMI for connecting locations that are greater than 100 meters apart, which two solutions can be utilized? (Choose two.)  
A. multimode fiber  
B. Fibre Channel  
C. HVDC transmission lines  
D. single-mode fiber  
E. serial RS-232  
F. Gigabit Ethernet 1000BASE-CX  
Answer: AD

**QUESTION 48** Which mode is used to exclusively look for unauthorized access points?  
A. monitor mode  
B. sniffer mode  
C. rogue detector mode  
D. local mode  
Answer: C

**QUESTION 49** Application servers require load balancing and security services. Where in the data center network should these services be provisioned?  
A. core  
B. aggregation  
C. Layer 3 access  
D. distribution  
Answer: B

**QUESTION 50** A data center is reaching its power and cooling capacity. What two virtualization technologies can address the problem by directly reducing the number of physical devices? (Choose two.)  
A. virtual switching systems  
B. virtual device contexts  
C. virtual servers  
D. virtual routing and forwarding  
E. virtual port channels  
F. virtual LANs  
Answer: BC

**QUESTION 51** A dynamically routed private line and a statically routed IPsec tunnel connect two offices. What routing configuration prefers the IPsec tunnel only in the event of a private line failure?  
A. floating static entry  
B. EIGRP variance  
C. bandwidth metric  
D. OSPF maximum paths  
Answer: A

**QUESTION 52** When designing a new enterprise campus network, what topology should be used for maximum scalability?  
A. flat  
B. three-layer  
C. star  
D. partial mesh  
E. full mesh  
Answer: B

**QUESTION 53** A spanning tree topology can be simplified by deploying what Cisco IOS technology in the distribution block?  
A. VDC  
B. vPCC  
C. Rapid PVST+  
D. VSSE  
E. Flex Links  
Answer: D

**QUESTION 54** An organization is deciding what routing protocol to use throughout their network. What must be considered if routing is to be performed at the access layer?  
A. reduced scalability of the network when introducing a large number of switch blocks into the routing table  
B. centralized management of access control lists at the distribution layer  
C. reliability when implementing routing over spanning-tree at the access layer  
D. performance differences between core, distribution and access layer equipment  
Answer: D

**QUESTION 55** What is the maximum RIPv2 hop count for a reachable route?  
A. 13  
B. 14  
C. 15  
D. 16  
Answer: C

**QUESTION 56** Which Cisco Wireless LAN Controller interface is used for out-of-band management?  
A. service port  
B. management port  
C. controller

portD. virtual port Answer: A QUESTION 57In which operation mode does the AP act as a dedicated sensor for location-based and intrusion detection services? A. monitor modeB. promiscuous modeC. discovery modeD. sniffer mode Answer: A  
QUESTION 58Which HSRP parameters must match, to ensure proper functionality? A. group parametersB. priority parametersC. preempt parametersD. tracking parameters Answer: A QUESTION 59What three primary sources of information are needed to perform a network audit? (Choose three.) A. existing documentationB. new documentationC. existing network management softwareD. new network management toolsE. management personnelF. technical personnel Answer: ACD  
QUESTION 60Which three layers comprise the traditional hierarchical model? (Choose three.) A. core layerB. distribution layerC. access layerD. aggregation layerE. network layerF. Internet layer Answer: ABC Thanks for the high quality 200-310 study guide. Will be back soon for more dumps. **200-310** new questions on Google Drive:  
<https://drive.google.com/open?id=0B3Syig5i8gpDclAzaXozN1E0NmM> **2017 Cisco 200-310** exam dumps (All 326 Q&As) from Lead2pass: <http://www.lead2pass.com/200-310.html> [100% Exam Pass Guaranteed]