CCNA Voice 640-461 Q&As – Miscellaneous Questions (1-5)

Section 8 ? Miscellaneous Questions QUESTION 1   When implementing a plan of action, what should you do?
A.   Make all of the changes at once to minimize the impact to users.   B.   Limit the impact of the changes to users.   C.   Completely remove access lists to ensure that they will not impact the changes.   D.   Even if a change adversely affects the users, keep moving forward with the plan of action.
Answer: BQUESTION 2   Refer to the exhibit. The error message was displayed when the administrator attempted to set the default user password in the user template to four digits long. Which option can rectify this issue?

A.   The minimum password length in Cisco Unity Connection should be at least five digits long.
B.   The password length needs to be configured under the Authentication Rules settings using the   Minimum Credential Length configuration field.   C.   The password length needs to be configured under the user template settings using the Minimum   Credential Length configuration field.   D.   The password length cannot be adjusted under the user template; the password length can only   be adjusted under the individual users.   Answer: B
QUESTION 3   Refer to the exhibit. The exhibit shows a partial screen shot for a Cisco Unified Client Services Framework device. If the username that is associated with this device is jdoe, what should the device name be?

A.   The device name should be JDOEUPC.   B.   The device name should be UPCJDOE.   C.   The device name should be JDOE.   D.   The device name should be UPCCUPC.   Answer: CD QUESTION 4   Which two types of device can the Cisco Unified Disaster Recovery use as a backup target? (Choose two.)   A.   DVD ROM drive   B.   FTP server C.   tape device   D.   TFTP server   E.   WebDAV server F.   SFTP server   G.   CD ROM   Answer: CF QUESTION 5   What is a benefit of

using FRF.12 in a Frame Relay network?   A.   provides a Layer 3 mechanism for reducing latency in the network   B.   fragments packets into equal sizes to reduce fixed-network delay   C.   reduces delay and jitter by expediting the transfer of smaller frames through the hardware transmit queue   D.   eliminates the need for prioritization of delay-sensitive traffic   Answer: B