

[Full Version 2016 New Lead2pass Cisco 300-360 Dumps Free Download (41-50)]

2016 November Cisco Official New Released 300-360 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! 2016 get prepared with fully updated Cisco 300-360 real exam questions and accurate answers for 300-360 exam. Lead2pass IT experts review the 300-360 newly added questions and offer correct Cisco 300-360 exam questions answers. 100% pass easily!

Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/300-360.html>

QUESTION 41 What is the optimal distance between APs for location services without considering the physical environment? A. 10 to 25 feet B. 90 to 120 feet C. 50 to 70 feet D. 80 to 100 feet Answer: C Explanation:

<http://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Mobility/emob41dg/emob41dg-wrapper/ch13Loca.html> QUESTION

42 A customer has deployed an N+N redundant wireless infrastructure. In this deployment, the access points have been salt and peppered between controllers. What configuration would be necessary to cut down on the use of mobility tunnels for voice clients? A. mobility anchor B. KIS based CACC. media session snooping D. re-anchor roamed voice clients Answer: D QUESTION

43 Which two best practices should be considered when a customer wants to purchase and implement Voice over Wireless for Cisco 7925 IP Phones? (Choose two.) A. Enable lower data rates for 2.4-GHz data WLAN and higher data rates for phones. B. Use a separate Cisco Wireless Lan Controller. C. Enable 802.1x and Cisco Centralized Key Management for phone authentication. D. Use dedicated Access Points only for Voice over Wireless. E. Set data for 2.4 GHz and voice for 5 GHz using separate SSIDs. Answer: CE QUESTION

44 What is a common cause for signal attenuation? A. Cinder block wall B. Office window C. Metal door D. Glass wall Answer: C QUESTION

45 The AP has been configured properly for a VoWLAN survey. The RF environment contains a noise of -87 to -90 dBm. What is the target value for the cell edge reading? A. -62 dBm B. -67 dBm C. -60 dBm D. -70 dBm Answer: B QUESTION

46 An 802.11n implementation is being discussed. Users are satisfied with the potential 300-450 Mbps throughput of new 802.11n APs. Which three bandwidth requirements are used to calculate per client bandwidth through an 802.11n AP network? (Choose three.) A. 450 Mbps throughput is the client max for 5-GHz radio. B. Channel bonding on 5 GHz is required for a client to have a 300 Mbps WiFi link. C. 300 Mbps throughput is the client max for 2.4-GHz radio. D. The remaining bandwidth is divided per device when more clients are connected to one AP. E. 100 Mbps Ethernet switch port is a potential bottleneck. F. CleanAir helps clear noise for 802.11n channel bonding to work. Answer: ACD QUESTION

47 An engineer is performing a predictive wireless design for a carpeted office space, which requires voice capability and location services. Which two requirements are inputs to the design? (Choose two.) A. overlapping -67 dBm coverage from three access points B. overlapping -75 dBm coverage from three access points C. overlapping -72 dBm coverage from two access points D. continuous -67 dBm coverage from one access point E. continuous -72 dBm coverage from one access point Answer: BD Explanation:

http://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Mobility/emob73dg/emob73/ch3_WLAN.html#pgfId-1000250 QUESTION

48 You have a customer that is building a new campus of four 3-story buildings that you have just completed the site survey for. The customer is interested in the amount of rack space they will need to allocate in either the building MDF or in the data center for controllers. Each building is going to require 75 APs to support voice and data. How should the controllers be deployed to provide the least number of controllers, the highest redundancy, and the easiest management? A. Use the centralized deployment method in the data center with the N + N redundancy method. B. Use the centralized deployment method in the data center with the N + 1 redundancy method. C. Use the centralized deployment method in the data center with the 1 + 1 redundancy method and client SSO. D. Use the distributed deployment method in each building MDF with the N + 1 redundancy method. E. Use the distributed deployment method in each building MDF with the N + N + 1 redundancy method. F. Use the distributed deployment method in each building MDF with the N + N redundancy method. Answer: C QUESTION

49 What are two advantages of conducting an active survey versus a passive survey when verifying RF coverage? (Choose two.) A. verifies packet loss B. verifies roaming C. verifies SNR D. verifies signal level E. verifies interferers Answer: AB QUESTION

50 An engineer is tuning RRM parameters to improve client connectivity. Which channel band results in the best 802.11n client compatibility? A. UNII-2B. UNII-2e C. UNII-3D. UNII-E. UNII-1 Answer: E Explanation: 802.11n operates on the same channel as 802.11a. For better compatibility with 802.11n clients, it is recommended to stay on lower channels (UNII-1 band).

<http://www.cisco.com/c/en/us/support/docs/wireless/4400-series-wireless-lancontrollers/108184config-802-11n-wlc.html> Latest 300-360 questions and answers from Cisco Exam Center offered by Lead2pass for free share now! Read and remember all real questions answers, Guarantee pass 300-360 real test 100% or full money back! 300-360 new questions on Google Drive:

<https://drive.google.com/open?id=0B3Syig5i8gpDaV9QUWIYNkdKUIE> 2016 Cisco 300-360 exam dumps (All 72 Q&As) from Lead2pass: <http://www.lead2pass.com/300-360.html> [100% Exam Pass Guaranteed]