

[Full Version Updated 642-035 New Questions From Lead2pass Free Downloading (81-100)]

2016 November Cisco Official New Released 642-035 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! I'm currently studying for Cisco exam 642-035. I do enjoy studying for exams. It's hard, but it's an excellent forcing function. I learn bits and pieces here and there now and then about this and that, but when I have an exam schedule for a set date, I have to study! And not only do I put in more hours, but I follow a more systematic approach. In this article, I'm going to share Lead2pass braindumps in case you too are studying and this method works for you. Following questions and answers are all new published by Cisco Official Exam Center: <http://www.lead2pass.com/642-035.html>

QUESTION 81 For a KVM session to be successful, which two of these need to be done? (Choose two.) A. The Cisco IMC IP address needs to be assigned on the Admin tab. B. The Cisco IMC IP address needs to be in the same subnet as the management IP. C. The Cisco IMC needs to be upgraded to the same version as the UCS Manager. D. The server needs to be fully discovered. Answer: AD

QUESTION 82 A customer is configuring SAN pin groups in a Cisco UCS domain. The customer notices that pinning is not working and traffic from the vHBA is not passing over the Fibre Channel uplink port. Which of these must be done for pinning to work correctly? A. Include the SAN pin group in a vHBA policy and then include the vHBA policy in the service profile that is assigned to that server. B. Include the SAN policy in the Cisco UCS Manager to match with pin groups on the fabric interconnect. C. The customer must have Cisco UCS Manager version 2.0 or above. D. Fibre Channel switch mode needs to be configured first. Answer: A

QUESTION 83 Refer to exhibit. A Cisco UCS admin is troubleshooting an issue with a vNIC not coming up on a blade. When looking at the CLI of the "Fabric Interconnect", the admin runs this command to view the status of the interface. Which option describes a possible reason why the interface is stuck in an "initializing" state?

```
aci-sol-calo-ucsb-A(nxos)# show interface vethernet 813
Vethernet813 is down (initializing)
  Bound Interface is port-channel1282
  Port description is server 1/1, VNIC Data-A
  Hardware is Virtual, address is 8c60.4f01.4420
  Port mode is trunk
  Speed is auto-speed
  Duplex mode is auto
 300 seconds input rate 0 bits/sec, 0 packets/sec
 300 seconds output rate 0 bits/sec, 0 packets/sec
Rx
  0 unicast packets  0 multicast packets  115 broadcast packets
 115 input packets  32934 bytes
  0 input packet drops
Tx
  0 unicast packets  29 multicast packets  0 broadcast packets
 29 output packets  8729 bytes
 0 flood packets
  0 output packet drops
```

A. The service profile is not applied to a blade. B. The VLANs defined on the vNIC are not defined on a matching uplink port. C. The uplink port is down. D. The QoS policy on the vNIC is invalid. E. The MTU on the vNIC is higher than the MTU configured in the QoS system class. Answer: C

QUESTION 84 Which two options are causes for failure of a Cisco C-Series server that is configured to boot from SAN? (Choose two.) A. The boot LUN ID is not 0. B. The iSCSI target is only available via one via one path through the network. C. C-Series does not support boot from SAN. D. The KVM dongle is attached to the front of the server with a USB stick installed. E. Under the FCoE properties on the vNIC adapter, the FCoE VLAN ID is set to 10. F. The boot table for fc0 has not been configured. Answer: DF

QUESTION 85 Which command on the Fabric Interconnect displays packet statistics for a given QoS group and MTU size? A. show policy-map interface ethernet x/y B. show queuing interface ethernet x/y C. show interface ethernet x/y D. show class-map type qos E. show interface queuing ethernet x/y Answer: B

QUESTION 86 A Cisco UCS admin is trying to integrate Cisco UCS Manager with Active Directory Authentication. After the configuration is done, the admin is still unable to log in using LDAP credentials. When running a debug on the Fabric Interconnect, this error is displayed: ldap_build_roles_and_locales_from_attr: No attr for usr profile Which step was missed in the configuration? A. The LDAP provider was not configured correctly. B. The proper RBAC role(s) were not assigned to the user. C. Cisco UCS Manager 2.1 is required for LDAP integration. D. The "Attribute" field in Cisco UCS was left blank. Answer: B

QUESTION 87 Which three requirements are needed to configure a blade to boot successfully from Fibre Channel? (Choose three.) A. zoning B. LUN masking C. WWPN device alias D. boot from SAN policy E. SAN connectivity policy F. port assignment G. target WWPN

needs to be set in the boot from SAN policy Answer: ABD QUESTION 88 Which description of a core file is true? A. It is generated by a system failure. B. It is generated by a process failure. C. It is generated by a component failure. D. It is generated by a hardware failure. Answer: B QUESTION 89 Which logs are used to troubleshoot hardware failure? A. system event log B. audit log C. accounting log D. gateway logs E. system log Answer: A QUESTION 90 A UCS Admin is trying to launch the KVM console but it is failing to launch. All IP Pools for mgmt are configured and the CIMC has an address in UCSM. They SSH to the fabric Interconnect and run an ethanalyzer while issuing a ping from their local PC to the KVM IP address. The ping is successful but they do not see the ICMP requests and replies displayed in the capture. Here is the filter they used: FIA(nxos)# ethanalyzer local interface mgmt display-filter icmp limit-captured-frames 0 What could be the reason pings are not seen in the capture and the KVM is failing to load? A. Java settings are preventing the KVM from loading B. There is a duplicate IP address for that CIMC address C. The switch upstream from the FI has the wrong vlan configured D. The CIMC IP pool is in the same subnet as the Fabric Interconnects mgmt 0 interface Answer: B QUESTION 91 Where do you configure users so that they cannot access resources that belong to other organizations? A. roles B. domain separation C. locals D. VDCs Answer: C QUESTION 92 What is the correct procedure to change Ethernet switching modes? A. Navigate to the subordinate Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", wait for it to come back up, and repeat on the primary FI. B. Navigate to either Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", and wait while both FIs reboot simultaneously. C. Navigate to either Fabric Interconnect in the GUI and transparently update the mode to switching. Repeat on the other Fabric Interconnect. D. Simply start using the switching features. The Fabric Interconnect automatically reconfigures to use Ethernet Switching Mode. Answer: B QUESTION 93 Which power policy should be chosen to maximize the performance of a Cisco UCS system with four PSUs and eight blades? A. non-redundant B. N+1 C. grid D. performance Answer: C QUESTION 94 Which option describes why the service profiles do not inherit changes from the template? A. The service profile is not compatible with the changes. B. The changes to the template have not been committed. C. It is an initial template. D. The service profile has disabled inheritance. Answer: C QUESTION 95 Which statement about Cisco UCS version compatibility is true? A. All bundles (A, B, and C) must be the same version. B. The B and C bundles must be the same revision. C. The A bundle can be one revision higher than the B/C bundles. D. The B/C bundles can be one revision higher than the A bundles. Answer: C QUESTION 96 Which feature on the Cisco IMC GUI allows you to view the last boot post operation? A. Firmware Management tab B. Bootstrap Process Recording C. Crash Recording D. Trusted Platform Module Answer: B QUESTION 97 Which option is a valid file extension for a CIMC configuration file? A. .xml B. .json C. .txt D. .exe E. .zip Answer: A QUESTION 98 Which three components are updated using the Host Upgrade Utility? (Choose three.) A. BIOS B. Network Adapter(s) C. Array Controller D. Cisco IMC E. LOM port F. UCSM G. Drive Firmware Answer: ABD QUESTION 99 Which option causes an operating system on a UCS device to consistently crash several minutes after booting? A. faulty power supply B. out-of-date network adapter firmware C. incompatible operating system driver D. incorrect boot order E. disabled trusted platform module Answer: C QUESTION 100 Which two statements about configuring a traffic monitoring session are true? (Choose two.) A. You can set a local VM as a traffic destination. B. You can have up to two active monitoring sessions simultaneously. C. An unlimited number of monitoring session can be stored. D. A newly created monitoring session is enabled by default. E. A destination port can also be a source port within the same session. F. A vHBA can be a source for either an Ethernet or Fibre Channel monitoring session, but not both. Answer: BF If you want to prepare for 642-035 exam in shortest time, with minimum effort but for most effective result, you can use Lead2pass 642-035 dump which simulates the actual testing environment and allows you to focus on various sections of 642-035 exam. Best of luck! 642-035 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDbEhhbDNSUlllZVk> 2016 Cisco 642-035 exam dumps (All 175 Q&As) from Lead2pass: <http://www.lead2pass.com/642-035.html> [100% Exam Pass Guaranteed]